PURITY [™] FG SYNTHETIC 46 FLUID



000003001293

Version 3.0 Revision Date 2016/10/03 Print Date		Print Date 2016/10/03	
SECTION 1. IDENTIFICATION			
Product name :	PURITY [™] FG SYNTHETIC 46 FLUID		
Product code :	PFSYNCOP5U, PFSYNCO, PFSYNCODRU		
Manufacturer or supplier's details	Petro-Canada Lubricants Inc. 2310 Lakeshore Road West Mississauga ON L5J 1K2 Canada		
Emergency telephone num- ber	Suncor Energy: +1 403-296-3000; Canutec Transportation: 1-888- 226-8832 (toll-free) or 613- 996-6666; Poison Control Centre: Consult local telephone directory for emergency number(s).		
Recommended use of the chen	nical and restrictions on use		
Recommended use :	PURITY FG Synthetic 46 Fluid is a fully lubricant.	v synthetic food grade	
	NSF H1 Registered.		
	This product complies with FDA 21 CFF with Incidental Food Contact [*] . It is inter industrial and food equipment. It should to the food product.	nded for application on	
Prepared by :	Product Safety: +1 905-804-4752		

SECTION 2. HAZARDS IDENTIFICATION

Emergency Overview

<u> </u>	
Appearance	liquid
11	
Colour	Yellow or brown.
Odour	Mild petroleum oil like.
Ououi	Wind perfored in like.

GHS Classification

Not a hazardous substance or mixture.

GHS label elements

Not a hazardous substance or mixture.

Potential Health Effects

Primary Routes of Entry

: Eye contact Ingestion

PURITY [™] FG SYNTHETIC 46 FLUID



00000001001

ersion 3.0	Revision Date 2016/10/03 Print Date 2016/10		
	Inhalation Skin contact		
Aggravated Medical Condi- tion	: None known.		
Other hazards			
None known.			
IARC	No component of this product present at levels greater than or equal to 0.1% is identified as probable, possible or confirmed human carcinogen by IARC.		
ACGIH	No component of this product present at levels greater than or equal to 0.1% is identified as a carcinogen or potential carcinogen by ACGIH.		
Hazardous components			
Hazardous components No hazardous ingredients			
No hazardous ingredients	RES		
•	RES : Move to fresh air. Artificial respiration and/or oxygen may be necessary. Seek medical advice.		
No hazardous ingredients CTION 4. FIRST AID MEASUR	: Move to fresh air. Artificial respiration and/or oxygen may be necessary.		
No hazardous ingredients CTION 4. FIRST AID MEASUR If inhaled	 Move to fresh air. Artificial respiration and/or oxygen may be necessary. Seek medical advice. In case of contact, immediately flush skin with plenty of wate for at least 15 minutes while removing contaminated clothing and shoes. Wash skin thoroughly with soap and water or use recognize skin cleanser. Wash clothing before reuse. 		

If swallowed	:	Rinse mouth with water. DO NOT induce vomiting unless directed to do so by a physi- cian or poison control center. Never give anything by mouth to an unconscious person. Seek medical advice.
Most important symptoms	:	First aider needs to protect himself.

and effects, both acute and

PURITY [™] FG SYNTHETIC 46 FLUID



Revision Date 2016/10/03



Print Date 2016/10/03

Version 3.0

delayed

SECTION 5. FIREFIGHTING MEASURES

Suitable extinguishing media	: Use extinguishing measures that are appropriate to local cir- cumstances and the surrounding environment.
Unsuitable extinguishing media	: No information available.
Specific hazards during fire- fighting	: Cool closed containers exposed to fire with water spray.
Hazardous combustion prod- ucts	: Carbon oxides (CO, CO2), smoke and irritating vapours as products of incomplete combustion.
Further information	: Prevent fire extinguishing water from contaminating surface water or the ground water system.

SECTION 6. ACCIDENTAL RELEASE MEASURES

Personal precautions, protec- tive equipment and emer- gency procedures	:	Use personal protective equipment. Ensure adequate ventilation. Evacuate personnel to safe areas. Material can create slippery conditions.
Environmental precautions	:	Do not allow uncontrolled discharge of product into the envi- ronment.
Methods and materials for containment and cleaning up	:	Prevent further leakage or spillage if safe to do so. Remove all sources of ignition. Soak up with inert absorbent material. Non-sparking tools should be used. Ensure adequate ventilation. Contact the proper local authorities.

SECTION 7. HANDLING AND STORAGE

Advice on safe handling	 For personal protection see section 8. Smoking, eating and drinking should be prohibited in the application area. Use only with adequate ventilation. In case of insufficient ventilation, wear suitable respiratory equipment. Avoid contact with skin, eyes and clothing. Do not ingest. Keep away from heat and sources of ignition. Keep container closed when not in use. 	
Conditions for safe storage	: Store in original container. Containers which are opened must be carefully resealed and	
Internet: lubricants.petro-canada.ca/msds Petro-Canada is a Suncor Energy business.	Page: 3 / ™ Trademark of Suncor Energy Inc. Used under licence	

PURITY [™] FG SYNTHETIC 46 FLUID

000003001293



Version 3.0	Revision Date 2016/10/03	Print Date 2016/10/03		
	kept upright to prevent leakage. Keep in a dry, cool and well-ventil	ated place.		
		Keep in properly labelled containers. To maintain product quality, do not store in heat or direct sun-		

SECTION 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

light.

Components with workplace control parameters			
Contains no substances with	occupational exposure limit values.		
Engineering measures	No special ventilation requirements. Good general ventilation should be sufficient to control worker exposure to airborne contaminants.		
Personal protective equip	ent		
Respiratory protection	: Use respiratory protection unless adequate local exhaust ventilation is provided or exposure assessment demonstrates that exposures are within recommended exposure guidelines. Respirator selection must be based on known or anticipated exposure levels, the hazards of the product and the safe working limits of the selected respirator.		
Filter type	: organic vapour filter		
Hand protection Material	: neoprene, nitrile, polyvinyl alcohol (PVA), Viton(R).		
Remarks	: Chemical-resistant, impervious gloves complying with an approved standard should be worn at all times when handling chemical products if a risk assessment indicates this is necessary.		
Eye protection	: Wear face-shield and protective suit for abnormal processing problems.		
Skin and body protection	: Choose body protection in relation to its type, to the concen- tration and amount of dangerous substances, and to the spe- cific work-place.		
Protective measures	: Wash contaminated clothing before re-use.		
Hygiene measures	 Remove and wash contaminated clothing and gloves, includ- ing the inside, before re-use. Wash face, hands and any exposed skin thoroughly after handling. 		

PURITY [™] FG SYNTHETIC 46 FLUID

000003001293

Version 3.0



Print Date 2016/10/03

SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES

Appearance	: liquid	
Colour	: Yellow or brown.	
Odour	: Mild petroleum oil like.	
Odour Threshold	: No data available	
рН	: No data available	
Pour point	: -60 °C (-76 °F)	
Boiling point/boiling range	: No data available	
Flash point	: 269 °C (516 °F) Method: Cleveland open cup	
Fire Point	: No data available	
Auto-Ignition Temperature	: No data available	
Evaporation rate	: No data available	
Flammability	: Low fire hazard. This material must be heated before igr will occur.	nition
Upper explosion limit	: No data available	
Lower explosion limit	: No data available	
Vapour pressure	: No data available	
Relative vapour density	: No data available	
Density	: 0.8337 kg/l (15 °C / 59 °F)	
Solubility(ies)		
Water solubility	: No data available	
Partition coefficient: n- octanol/water	: No data available	
Viscosity		
Viscosity, kinematic	: 46.3 cSt (40 °C / 104 °F)	
	7.71 cSt (100 °C / 212 °F)	
Explosive properties	: Do not pressurise, cut, weld, braze, solder, drill, grind or pose containers to heat or sources of ignition.	ex-

SECTION 10. STABILITY AND REACTIVITY

Possibility of hazardous reac-	:	Hazardous polymerisation does not occur.
tions		Stable under normal conditions.

PURITY [™] FG SYNTHETIC 46 FLUID



000003001293

Version 3.0	Revision Date 2016/10/03	Print Date 2016/10/03
Conditions to avoid	: No data available	
Incompatible materials	: Reactive with oxidising agents.	
Hazardous decomposition products	: May release COx, aldehydes, smo when heated to decomposition.	oke and irritating vapours

SECTION 11. TOXICOLOGICAL INFORMATION

Information on likely routes of Eye contact Ingestion Inhalation Skin contact	of	exposure		
Acute toxicity				
Product: Acute oral toxicity	:	Remarks: No data available		
Acute inhalation toxicity	:	Remarks: No data available		
Acute dermal toxicity	:	Remarks: No data available		
Skin corrosion/irritation				
<u>Product:</u> Remarks: No data available				
Serious eye damage/eye irrit	ati	on		
<u>Product:</u> Remarks: No data available				
Respiratory or skin sensitisation No data available				
Germ cell mutagenicity No data available				
Carcinogenicity				
No data available				
Reproductive toxicity				
No data available				
STOT - single exposure No data available				
STOT - repeated exposure				

No data available

PURITY [™] FG SYNTHETIC 46 FLUID

000003001293

Version 3.0

Print Date 2016/10/03

SECTION 12. ECOLOGICAL INFORMATION

Ecotoxicity	
<u>Product:</u> Toxicity to fish	: Remarks: No data available
Toxicity to daphnia and other aquatic invertebrates	: Remarks: No data available
Toxicity to algae	: Remarks: No data available
Toxicity to bacteria	: Remarks: No data available
Persistence and degradabili	ty
Product:	
Biodegradability	: Remarks: No data available
Bioaccumulative potential No data available	
Mobility in soil	
No data available	
Other adverse effects	
No data available	

SECTION 13. DISPOSAL CONSIDERATIONS

Disposal methods	
Waste from residues	 The product should not be allowed to enter drains, water courses or the soil. Offer surplus and non-recyclable solutions to a licensed disposal company. Waste must be classified and labelled prior to recycling or disposal. Send to a licensed waste management company. Dispose of product residue in accordance with the instructions of the person responsible for waste disposal.

SECTION 14. TRANSPORT INFORMATION

International Regulations

IATA-DGR

Not regulated as a dangerous good

IMDG-Code

Not regulated as a dangerous good Internet: lubricants.petro-canada.ca/msds Petro-Canada is a Suncor Energy business.



PURITY [™] FG SYNTHETIC 46 FLUID



Version 3.0

Revision Date 2016/10/03

Print Date 2016/10/03

Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code Not applicable for product as supplied.

National Regulations

TDG

Not regulated as a dangerous good

SECTION 15. REGULATORY INFORMATION

This product has been classified according to the hazard criteria of the CPR and the MSDS contains all of the information required by the CPR.

The components of this product are reported in the following inventories:

DSL PICCS TSCA	On the inventory, or in compliance with the inventory On the inventory, or in compliance with the inventory All chemical substances in this product are either listed on the TSCA Inventory or are in compliance with a TSCA Inventory exemption.
AICS	On the inventory, or in compliance with the inventory
IECSC	On the inventory, or in compliance with the inventory
ENCS	On the inventory, or in compliance with the inventory
KECI	On the inventory, or in compliance with the inventory
EINECS	On the inventory, or in compliance with the inventory

SECTION 16. OTHER INFORMATION

For Copy of SDS	:	Internet: lubricants.petro-canada.ca/msds Western Canada, telephone: 1-800-661-1199; fax: 1-800-378- 4518 Ontario & Central Canada, telephone: 1-800-268-5850; fax: 1- 800-201-6285 Quebec & Eastern Canada, telephone: 1-800-576-1686; fax: 1-800-201-6285 For Product Safety Information: 1 905-804-4752
Prepared by	:	Product Safety: +1 905-804-4752
Revision Date	:	2016/10/03

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

