## PRECISION TM/MC XL EP2



#### 000003000891

Version 4.3 Revision Date 2017/09/12 Print Date 2017/09/12

#### **SECTION 1. IDENTIFICATION**

Product name : PRECISION TM/MC XL EP2

Product code : PXL2P17, PXL2KGL, PXL2DRL, PXL2CBG, PXL2C30,

PXL2, PXL2BLK

Manufacturer or supplier's details

Petro-Canada Lubricants Inc. 2310 Lakeshore Road West Mississauga ON L5J 1K2

Canada

Emergency telephone num-

ber

Petro-Canada Lubricants Inc.: +1 905-403-5770; CHEMTREC Transport Emergency: 1-800-424-9300;

Poison Control Centre: Consult local telephone directory for

emergency number(s).

#### Recommended use of the chemical and restrictions on use

Recommended use : PRECISION XL EP greases are high performance, long life,

EP greases designed for trouble-free lubrication of a wide

range of automotive and industrial equipment.

Prepared by : Product Safety: +1 905-804-4752

### **SECTION 2. HAZARDS IDENTIFICATION**

#### **Emergency Overview**

Appearance	Stringy, smooth, semi-solid.
Colour	green
Odour	Mild grease like.

#### **GHS Classification**

Not a hazardous substance or mixture.

#### **GHS label elements**

Not a hazardous substance or mixture.

#### **Potential Health Effects**

Primary Routes of Entry : Eye contact

Ingestion Inhalation Skin contact

Aggravated Medical Condi-

tion

: None known.

## PRECISION TM/MC XL EP2



#### 000003000891

Version 4.3 Revision Date 2017/09/12 Print Date 2017/09/12

Other hazards
None known.

IARC No component of this product present at levels greater than or

equal to 0.1% is identified as probable, possible or confirmed

human carcinogen by IARC.

**ACGIH** No component of this product present at levels greater than or

equal to 0.1% is identified as a carcinogen or potential carcino-

gen by ACGIH.

#### **SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS**

Substance / Mixture : Mixture

#### **Hazardous components**

Chemical name	CAS-No.	Concentration
Paraffin oils	8012-95-1	70 - 90 %
	0012-95-1	10 - 90 /6
lubricating oils (petroleum), C20-50, hydrotreat-	72623-85-9	30 - 50 %
ed neutral oil-based, high viscosity		
distillates (petroleum), solvent-dewaxed heavy	64742-65-0	10 - 20 %
paraffinic		
calcium carbonate	471-34-1	5 - 10 %

#### **SECTION 4. FIRST AID MEASURES**

If inhaled : Move to fresh air.

Artificial respiration and/or oxygen may be necessary.

Seek medical advice.

In case of skin contact : In case of contact, immediately flush eyes or skin with plenty

of water for at least 15 minutes while removing contaminated

clothing and shoes.

Wash skin thoroughly with soap and water or use recognized

skin cleanser.

Wash clothing before reuse.

Seek medical advice.

In the event of a known, or potential, high pressure injection injury, worker should obtain immediate medical evaluation.

In case of eye contact : Remove contact lenses.

Rinse immediately with plenty of water, also under the eyelids,

for at least 15 minutes. Obtain medical attention.

If swallowed : Rinse mouth with water.

DO NOT induce vomiting unless directed to do so by a physi-

cian or poison control center.

Never give anything by mouth to an unconscious person.

Seek medical advice.

## PRECISION TM/MC XL EP2



#### 000003000891

Version 4.3 Revision Date 2017/09/12 Print Date 2017/09/12

Most important symptoms and effects, both acute and delayed

: First aider needs to protect himself.

#### **SECTION 5. FIREFIGHTING MEASURES**

Suitable extinguishing media : Use extinguishing measures that are appropriate to local cir-

cumstances and the surrounding environment.

Unsuitable extinguishing

media

: No information available.

Specific hazards during fire-

fighting

: Cool closed containers exposed to fire with water spray.

Hazardous combustion prod-

ucts

Carbon oxides (CO, CO2), sulphur oxides (SOx), nitrogen oxides (NOx), phosphorus oxides (POx), sulphur compounds (H2S), calcium oxides (CaOx), antimony oxides (SbOx), potassium oxide, aldehydes, sulfides, alkyl mercaptans, diphenylamine, alkenes, smoke and irritating vapours as products

of incomplete combustion.

Further information : Prevent fire extinguishing water from contaminating surface

water or the ground water system.

#### **SECTION 6. ACCIDENTAL RELEASE MEASURES**

Personal precautions, protective equipment and emer-

gency procedures

: Use personal protective equipment.

Ensure adequate ventilation. Evacuate personnel to safe areas. Material can create slippery conditions.

Environmental precautions : If the product contaminates rivers and lakes or drains inform

respective authorities.

Methods and materials for containment and cleaning up

Prevent further leakage or spillage if safe to do so.

Remove all sources of ignition.

Soak up with inert absorbent material. Non-sparking tools should be used. Ensure adequate ventilation. Contact the proper local authorities.

#### **SECTION 7. HANDLING AND STORAGE**

Advice on safe handling : For personal protection see section 8.

Smoking, eating and drinking should be prohibited in the ap-

plication area.

In case of insufficient ventilation, wear suitable respiratory

equipment.

Avoid contact with skin, eyes and clothing.

## PRECISION TM/MC XL EP2



#### 000003000891

Version 4.3 Revision Date 2017/09/12 Print Date 2017/09/12

Do not ingest.

Keep away from heat and sources of ignition. Keep container closed when not in use.

Conditions for safe storage : Store in original container.

Containers which are opened must be carefully resealed and

kept upright to prevent leakage.

Keep in a dry, cool and well-ventilated place.

Keep in properly labelled containers.

To maintain product quality, do not store in heat or direct sun-

light.

#### **SECTION 8. EXPOSURE CONTROLS/PERSONAL PROTECTION**

#### Components with workplace control parameters

Components	CAS-No.	Value type (Form of exposure)	Control parameters / Permissible concentration	Basis
lubricating oils (petroleum), C20-50, hydrotreated neutral oil-based, high viscosity	72623-85-9	TWA (Mist)	5 mg/m3	CA AB OEL
		STEL (Mist)	10 mg/m3	CA AB OEL
		TWAEV (Mist)	5 mg/m3	CA QC OEL
		STEV (Mist)	10 mg/m3	CA QC OEL
		TWA (Inhal- able fraction)	5 mg/m3	ACGIH
calcium carbonate	471-34-1	TWAEV (to- tal dust)	10 mg/m3	CA QC OEL

**Engineering measures** 

: No special ventilation requirements. Good general ventilation should be sufficient to control worker exposure to airborne contaminants.

#### Personal protective equipment

Respiratory protection : Use respiratory protection unless adequate local exhaust

ventilation is provided or exposure assessment demonstrates that exposures are within recommended exposure guidelines. Respirator selection must be based on known or anticipated exposure levels, the hazards of the product and the safe

working limits of the selected respirator.

Filter type : organic vapour filter

Hand protection

Material : neoprene, nitrile, polyvinyl alcohol (PVA), Viton(R).

Remarks : Chemical-resistant, impervious gloves complying with an

approved standard should be worn at all times when handling chemical products if a risk assessment indicates this is nec-

essary.

## PRECISION TM/MC XL EP2



#### 000003000891

Version 4.3 Revision Date 2017/09/12 Print Date 2017/09/12

Eye protection : Wear face-shield and protective suit for abnormal processing

problems.

Skin and body protection : Choose body protection in relation to its type, to the concen-

tration and amount of dangerous substances, and to the spe-

cific work-place.

Protective measures : Wash hands and face before breaks and immediately after

handling the product.

Wash contaminated clothing before re-use.

Ensure that eyewash station and safety shower are proximal

to the work-station location.

Hygiene measures : Wash face, hands and any exposed skin thoroughly after

handling.

Remove and wash contaminated clothing and gloves, includ-

ing the inside, before re-use.

#### **SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES**

Appearance : Stringy, smooth, semi-solid.

Colour : green

Odour : Mild grease like.

Odour Threshold : No data available
pH : No data available

Pour point : -12 °C (10 °F)Base Fluid Blend

Boiling point/boiling range : No data available Flash point : 290 °C (554 °F)

Method: Cleveland open cup

Base Fluid Blend

Fire Point : 300 °C (572 °F)

Base Fluid Blend

Auto-Ignition Temperature : No data available Evaporation rate : No data available

Flammability : Low fire hazard. This material must be heated before ignition

will occur.

Upper explosion limit : No data available
Lower explosion limit : No data available
Vapour pressure : No data available

Relative vapour density

No data available

Density : 0.9083 kg/l (15 °C / 59 °F)

Solubility(ies)

Water solubility : insoluble

## PRECISION TM/MC XL EP2



#### 000003000891

Version 4.3 Revision Date 2017/09/12 Print Date 2017/09/12

Partition coefficient: n-

octanol/water

: No data available

Viscosity

Viscosity, kinematic : 219.9 cSt (40 °C / 104 °F)

Base Fluid Blend

17.9 cSt (100 °C / 212 °F)

Base Fluid Blend

Explosive properties : Do not pressurise, cut, weld, braze, solder, drill, grind or ex-

pose containers to heat or sources of ignition.

#### **SECTION 10. STABILITY AND REACTIVITY**

Possibility of hazardous reac-

tions

: Hazardous polymerisation does not occur.

Stable under normal conditions.

Conditions to avoid : No data available

Incompatible materials : Reactive with oxidising agents, acids, alkalis and reducing

agents.

Hazardous decomposition

products

: May release COx, NOx, SOx, POx, H2S, CaOx, SbOx, KOx,

aldehydes, sulfides, alkyl mercaptans, diphenylamine, alkenes, ammonia, metal oxides, halogenated compounds, smoke and irritating vapours when heated to decomposition.

#### **SECTION 11. TOXICOLOGICAL INFORMATION**

### Information on likely routes of exposure

Eye contact Ingestion Inhalation Skin contact

#### **Acute toxicity**

**Product:** 

Acute oral toxicity : Remarks: No data available

Acute inhalation toxicity : Remarks: No data available

Acute dermal toxicity : Remarks: No data available

### Components:

lubricating oils (petroleum), C20-50, hydrotreated neutral oil-based, high viscosity:

Acute oral toxicity : LD50 (Rat): > 5,000 mg/kg,

Acute inhalation toxicity : LC50 (Rat): > 5.2 mg/l

Exposure time: 4 h

Test atmosphere: dust/mist

Page: 6 / 9

## PRECISION TM/MC XL EP2



#### 000003000891

Version 4.3 Revision Date 2017/09/12 Print Date 2017/09/12

Acute dermal toxicity : LD50 (Rabbit): > 2,000 mg/kg,

**distillates (petroleum), solvent-dewaxed heavy paraffinic:**Acute oral toxicity : LD50 (Rat): > 5,000 mg/kg,

Acute dermal toxicity : LD50 (Rabbit): > 5,000 mg/kg,

calcium carbonate:

Acute oral toxicity : LD50 (Rat): > 2,000 mg/kg,

Skin corrosion/irritation

**Product:** 

Remarks: No data available

Serious eye damage/eye irritation

**Product:** 

Remarks: No data available

Respiratory or skin sensitisation

No data available

Germ cell mutagenicity

No data available

Carcinogenicity

No data available

Reproductive toxicity

No data available

STOT - single exposure

No data available

STOT - repeated exposure

No data available

### **SECTION 12. ECOLOGICAL INFORMATION**

### **Ecotoxicity**

**Product:** 

Toxicity to fish

Remarks: No data available

Toxicity to daphnia and other

aquatic invertebrates

Remarks: No data available

## PRECISION TM/MC XL EP2



#### 000003000891

Version 4.3 Revision Date 2017/09/12 Print Date 2017/09/12

Toxicity to algae

Remarks: No data available

Toxicity to bacteria : Remarks: No data available

Persistence and degradability

**Product:** 

Biodegradability : Remarks: No data available

Bioaccumulative potential

No data available

Mobility in soil

No data available

Other adverse effects

No data available

#### **SECTION 13. DISPOSAL CONSIDERATIONS**

**Disposal methods** 

Waste from residues : The product should not be allowed to enter drains, water

courses or the soil.

Offer surplus and non-recyclable solutions to a licensed dis-

posal company.

Waste must be classified and labelled prior to recycling or

disposal.

Send to a licensed waste management company.

Dispose of product residue in accordance with the instructions

of the person responsible for waste disposal.

#### **SECTION 14. TRANSPORT INFORMATION**

### International Regulations

IATA-DGR

Not regulated as a dangerous good

**IMDG-Code** 

Not regulated as a dangerous good

Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

Not applicable for product as supplied.

**National Regulations** 

TDG

Not regulated as a dangerous good

## PRECISION TM/MC XL EP2



#### 000003000891

Version 4.3 Revision Date 2017/09/12 Print Date 2017/09/12

#### **SECTION 15. REGULATORY INFORMATION**

This product has been classified according to the hazard criteria of the CPR and the MSDS contains all of the information required by the CPR.

#### The components of this product are reported in the following inventories:

**DSL** On the inventory, or in compliance with the inventory

TSCA All chemical substances in this product are either listed on the

TSCA Inventory or are in compliance with a TSCA Inventory

exemption.

**ELINCS** On the inventory, or in compliance with the inventory **IECSC** On the inventory, or in compliance with the inventory

#### **SECTION 16. OTHER INFORMATION**

For Copy of SDS : Internet: lubricants.petro-canada.com/sds

Western Canada, telephone: 1-800-661-1199; fax: 1-800-378-

4518

Ontario & Central Canada, telephone: 1-800-268-5850; fax: 1-

800-201-6285

Quebec & Eastern Canada, telephone: 1-800-576-1686; fax:

1-800-201-6285

For Product Safety Information: 1 905-804-4752

Prepared by : Product Safety: +1 905-804-4752

Revision Date : 2017/09/12

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.