

# SAFETY DATA SHEET

## PURITY™ FG SYNTHETIC EP GEAR FLUID 220



000003001100

Version 4.0

Revision Date 2016/10/03

Print Date 2016/10/03

### SECTION 1. IDENTIFICATION

Product name : PURITY™ FG SYNTHETIC EP GEAR FLUID 220

Product code : PFSN220P20, PFSN220, PFSN220DRU

Manufacturer or supplier's details

Petro-Canada Lubricants Inc.  
2310 Lakeshore Road West  
Mississauga ON L5J 1K2  
Canada

Emergency telephone number : Suncor Energy: +1 403-296-3000;  
Canutec Transportation: 1-888- 226-8832 (toll-free) or 613-996-6666;  
Poison Control Centre: Consult local telephone directory for emergency number(s).

#### Recommended use of the chemical and restrictions on use

Recommended use : PURITY FG Synthetic EP Gear Fluid 220 is a food grade lubricant.

NSF H1 Registered.

This product complies with FDA 21 CFR 178.3570 "Lubricants with Incidental Food Contact". It is intended for application on industrial and food equipment. It should not be added directly to the food product.

Prepared by : Product Safety: +1 905-804-4752

### SECTION 2. HAZARDS IDENTIFICATION

#### Emergency Overview

Appearance	liquid
Colour	colourless
Odour	mild

#### GHS Classification

Not a hazardous substance or mixture.

#### GHS label elements

Not a hazardous substance or mixture.

#### Potential Health Effects

Primary Routes of Entry : Eye contact  
Ingestion

# SAFETY DATA SHEET

## PURITY™ FG SYNTHETIC EP GEAR FLUID 220



000003001100

Version 4.0

Revision Date 2016/10/03

Print Date 2016/10/03

Inhalation  
Skin contact

Aggravated Medical Condition : None known.

### Other hazards

None known.

### IARC

No component of this product present at levels greater than or equal to 0.1% is identified as probable, possible or confirmed human carcinogen by IARC.

### ACGIH

No component of this product present at levels greater than or equal to 0.1% is identified as a carcinogen or potential carcinogen by ACGIH.

---

## SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS

Substance / Mixture : Mixture

### Hazardous components

No hazardous ingredients

---

## SECTION 4. FIRST AID MEASURES

- If inhaled : Move to fresh air.  
Artificial respiration and/or oxygen may be necessary.  
Seek medical advice.
- In case of skin contact : In case of contact, immediately flush skin with plenty of water for at least 15 minutes while removing contaminated clothing and shoes.  
Wash skin thoroughly with soap and water or use recognized skin cleanser.  
Wash clothing before reuse.  
Seek medical advice.
- In case of eye contact : Remove contact lenses.  
Rinse immediately with plenty of water, also under the eyelids, for at least 15 minutes.  
Obtain medical attention.
- If swallowed : Rinse mouth with water.  
DO NOT induce vomiting unless directed to do so by a physician or poison control center.  
Never give anything by mouth to an unconscious person.  
Seek medical advice.
- Most important symptoms and effects, both acute and : First aider needs to protect himself.

# SAFETY DATA SHEET

## PURITY™ FG SYNTHETIC EP GEAR FLUID 220



000003001100

Version 4.0

Revision Date 2016/10/03

Print Date 2016/10/03

delayed

---

### SECTION 5. FIREFIGHTING MEASURES

- Suitable extinguishing media : Use extinguishing measures that are appropriate to local circumstances and the surrounding environment.
- Unsuitable extinguishing media : No information available.
- Specific hazards during fire-fighting : Cool closed containers exposed to fire with water spray.
- Hazardous combustion products : Carbon oxides (CO, CO<sub>2</sub>), smoke and irritating vapours as products of incomplete combustion.
- Further information : Prevent fire extinguishing water from contaminating surface water or the ground water system.

---

### SECTION 6. ACCIDENTAL RELEASE MEASURES

- Personal precautions, protective equipment and emergency procedures : Use personal protective equipment.  
Ensure adequate ventilation.  
Evacuate personnel to safe areas.  
Material can create slippery conditions.
- Environmental precautions : Do not allow uncontrolled discharge of product into the environment.
- Methods and materials for containment and cleaning up : Prevent further leakage or spillage if safe to do so.  
Remove all sources of ignition.  
Soak up with inert absorbent material.  
Non-sparking tools should be used.  
Ensure adequate ventilation.  
Contact the proper local authorities.

---

### SECTION 7. HANDLING AND STORAGE

- Advice on safe handling : For personal protection see section 8.  
Smoking, eating and drinking should be prohibited in the application area.  
Use only with adequate ventilation.  
In case of insufficient ventilation, wear suitable respiratory equipment.  
Avoid contact with skin, eyes and clothing.  
Do not ingest.  
Keep away from heat and sources of ignition.  
Keep container closed when not in use.
- Conditions for safe storage : Store in original container.  
Containers which are opened must be carefully resealed and

# SAFETY DATA SHEET

## PURITY™ FG SYNTHETIC EP GEAR FLUID 220



000003001100

Version 4.0

Revision Date 2016/10/03

Print Date 2016/10/03

kept upright to prevent leakage.  
Keep in a dry, cool and well-ventilated place.  
Keep in properly labelled containers.  
To maintain product quality, do not store in heat or direct sunlight.

### SECTION 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

#### Components with workplace control parameters

Contains no substances with occupational exposure limit values.

**Engineering measures** : No special ventilation requirements. Good general ventilation should be sufficient to control worker exposure to airborne contaminants.

#### Personal protective equipment

**Respiratory protection** : Use respiratory protection unless adequate local exhaust ventilation is provided or exposure assessment demonstrates that exposures are within recommended exposure guidelines. Respirator selection must be based on known or anticipated exposure levels, the hazards of the product and the safe working limits of the selected respirator.

**Filter type** : organic vapour filter

**Hand protection**  
**Material** : neoprene, nitrile, polyvinyl alcohol (PVA), Viton(R).

**Remarks** : Chemical-resistant, impervious gloves complying with an approved standard should be worn at all times when handling chemical products if a risk assessment indicates this is necessary.

**Eye protection** : Wear face-shield and protective suit for abnormal processing problems.

**Skin and body protection** : Choose body protection in relation to its type, to the concentration and amount of dangerous substances, and to the specific work-place.

**Protective measures** : Wash contaminated clothing before re-use.

**Hygiene measures** : Remove and wash contaminated clothing and gloves, including the inside, before re-use.  
Wash face, hands and any exposed skin thoroughly after handling.

# SAFETY DATA SHEET

## PURITY™ FG SYNTHETIC EP GEAR FLUID 220



000003001100

Version 4.0

Revision Date 2016/10/03

Print Date 2016/10/03

---

### SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES

Appearance	: liquid
Colour	: colourless
Odour	: mild
Odour Threshold	: No data available
pH	: No data available
Pour point	: -43 °C (-45 °F)
Boiling point/boiling range	: > 315.6 °C (> 600.1 °F)
Flash point	: 268 °C (514 °F) Method: Cleveland open cup
Fire Point	: No data available
Auto-Ignition Temperature	: No data available
Evaporation rate	: No data available
Flammability	: Low fire hazard. This material must be heated before ignition will occur.
Upper explosion limit	: No data available
Lower explosion limit	: No data available
Vapour pressure	: No data available
Relative vapour density	: No data available
Density	: 0.847 kg/l (15 °C / 59 °F)
Solubility(ies)	
Water solubility	: insoluble
Partition coefficient: n-octanol/water	: No data available
Viscosity	
Viscosity, kinematic	: 229 cSt (40 °C / 104 °F)  24.0 cSt (100 °C / 212 °F)
Explosive properties	: Do not pressurise, cut, weld, braze, solder, drill, grind or expose containers to heat or sources of ignition.

---

### SECTION 10. STABILITY AND REACTIVITY

Possibility of hazardous reac- : Hazardous polymerisation does not occur.

# SAFETY DATA SHEET

## PURITY™ FG SYNTHETIC EP GEAR FLUID 220



000003001100

Version 4.0

Revision Date 2016/10/03

Print Date 2016/10/03

---

tions	Stable under normal conditions.
Conditions to avoid	: No data available
Incompatible materials	: Reactive with oxidising agents.
Hazardous decomposition products	: May release CO <sub>x</sub> , smoke and irritating vapours when heated to decomposition.

---

### SECTION 11. TOXICOLOGICAL INFORMATION

#### Information on likely routes of exposure

Eye contact  
Ingestion  
Inhalation  
Skin contact

#### Acute toxicity

##### Product:

Acute oral toxicity : Remarks: No data available  
Acute inhalation toxicity : Remarks: No data available  
Acute dermal toxicity : Remarks: No data available

#### Skin corrosion/irritation

##### Product:

Remarks: No data available

#### Serious eye damage/eye irritation

##### Product:

Remarks: No data available

#### Respiratory or skin sensitisation

No data available

#### Germ cell mutagenicity

No data available

#### Carcinogenicity

No data available

#### Reproductive toxicity

No data available

#### STOT - single exposure

No data available

#### STOT - repeated exposure

# SAFETY DATA SHEET

## PURITY™ FG SYNTHETIC EP GEAR FLUID 220



000003001100

Version 4.0

Revision Date 2016/10/03

Print Date 2016/10/03

No data available

---

### SECTION 12. ECOLOGICAL INFORMATION

#### Ecotoxicity

##### Product:

Toxicity to fish :  
Remarks: No data available

Toxicity to daphnia and other :  
aquatic invertebrates Remarks: No data available

Toxicity to algae :  
Remarks: No data available

Toxicity to bacteria : Remarks: No data available

#### Persistence and degradability

##### Product:

Biodegradability : Remarks: No data available

#### Bioaccumulative potential

No data available

#### Mobility in soil

No data available

#### Other adverse effects

No data available

---

### SECTION 13. DISPOSAL CONSIDERATIONS

#### Disposal methods

Waste from residues : The product should not be allowed to enter drains, water courses or the soil.  
Offer surplus and non-recyclable solutions to a licensed disposal company.  
Waste must be classified and labelled prior to recycling or disposal.  
Send to a licensed waste management company.  
Dispose of product residue in accordance with the instructions of the person responsible for waste disposal.

---

### SECTION 14. TRANSPORT INFORMATION

#### International Regulations

##### IATA-DGR

Not regulated as a dangerous good

# SAFETY DATA SHEET

## PURITY™ FG SYNTHETIC EP GEAR FLUID 220



000003001100

Version 4.0

Revision Date 2016/10/03

Print Date 2016/10/03

### IMDG-Code

Not regulated as a dangerous good

### Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

Not applicable for product as supplied.

### National Regulations

### TDG

Not regulated as a dangerous good

---

## SECTION 15. REGULATORY INFORMATION

This product has been classified according to the hazard criteria of the CPR and the MSDS contains all of the information required by the CPR.

### The components of this product are reported in the following inventories:

<b>DSL</b>	On the inventory, or in compliance with the inventory
<b>TSCA</b>	All chemical substances in this product are either listed on the TSCA Inventory or are in compliance with a TSCA Inventory exemption.
<b>AICS</b>	On the inventory, or in compliance with the inventory
<b>IECSC</b>	On the inventory, or in compliance with the inventory
<b>EINECS</b>	On the inventory, or in compliance with the inventory

---

## SECTION 16. OTHER INFORMATION

For Copy of SDS : Internet: [lubricants.petro-canada.ca/msds](http://lubricants.petro-canada.ca/msds)  
Western Canada, telephone: 1-800-661-1199; fax: 1-800-378-4518  
Ontario & Central Canada, telephone: 1-800-268-5850; fax: 1-800-201-6285  
Quebec & Eastern Canada, telephone: 1-800-576-1686; fax: 1-800-201-6285  
For Product Safety Information: 1 905-804-4752

Prepared by : Product Safety: +1 905-804-4752

Revision Date : 2016/10/03

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.